



## **Specifications**

Model	W.HFS22	W.HFS23
Height	725mm	725mm
Width	705mm	1030mm
Depth	600mm*	600mm*
Power	1.5kW	2.4kW

10A plug & lead 10A plug & lead fitted fitted

W.HFS24 W.HFS25 Model Height 725mm 725mm Width 1355mm 1680mm Depth 600mm\* 600mm<sup>3</sup> 3.0kW 3.3kW Power


15A plug & lead 15A plug & lead


fitted fitted

W.HFS26 Model 725mm Height Width 2005mm Depth 600mm\* 3.6kW Power

15A plug & lead fitted

\*Dimension does not include tap








## **Product Information:**

- Air insulated tank with double skin stainless steel construction
- All units complete with rear sliding doors on rollers for council compliance
- In-tank temperature probes for accurate measurement and lower running costs
- Multiple element design for reliable operation and even temperature
- Designed for wet operation
- Improved infra-red heat lamp configuration for optimum heat & light
- Toughened glass on all sides for maximum safety
- Rectangular base to easily drop in to bench cut-out
- Optimum visibility of product no unsightly corner post to front
- Mechanical thermostat control with temperature gauge
- Designed to run between 70°C 80°C
- Takes gastronorm pans up to 100mm deep (sold separately)
- Other pan sizes and combinations available
- Available in a range of sizes from 2-6 modules
- Available in a variety of other profiles, with matching cold food displays
- Wide range of functional accessories available

## Note:

- Not recommended for the display of chickens or roast meats
- All Woodson units are designed for use with Woodson pans. Other suppliers pans may fit, however this is not guaranteed.







Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: B - 29/08/2022 - 02

www.stoddart.com.au www.stoddart.co.nz

